

## Standard tolerances

**GERN GLAS**

Industrivej 4, DK-8641 Sorring  
+45 86 95 75 44

www.gernglas.com  
post@gernglas.com  
CVR: DK21698075

Danske Bank DKK konto:  
3647-3647487157  
IBAN DK35 3000 3647 4871 57

Danske Bank EUR konto:  
3647-3647541224  
IBAN DK76 3000 3647 5412 24

### Our standard tolerances are:

|                               |     |  |
|-------------------------------|-----|--|
| Length/width:                 | +/- | 1 mm                                       |
| Length/width:                 | +/- | 0,5 mm (CNC articles)                      |
| Square ness:                  |     |  |
| Up to 1 meter length:         | +/- | 1 mm **                                    |
| Between 1 and 2 m length:     | +/- | 1,5 mm ***                                 |
| Placement of holes:           | +/- | 1 mm (For handles with 2 holes: +/-0,5 mm) |
| Dimension of holes:           | +/- | 0,3 mm                                     |
| Placement of holes from edge: |     | Minimum twice the thickness of the glass   |
| Thickness of glass:           | +/- | 0,2 mm                                     |

\*\* This means, there can be a difference of the mutual measure of diagonal at 2 mm.

\*\*\* This means, there can be a difference of the mutual measure of diagonal at 3 mm.

Tempering test: In a square of 50x50 mm there must be minimum 40 pieces.

Bending: Max 30 mm per meter glass. Locally over max 300 mm max 0,5 mm.

21-12-2017

GERN GLAS A/S

